

# PURITY C Filter Head



## One Filter Head System for all applications

By providing various connections and bypass settings, BRITA Professional filter heads form the basis for the PURITY C filter cartridge range. Choose between the filter head that enables a variable bypass setting of 0 - 70 %, or a filter head with a fixed bypass setting of 0 % or 30 % (all available with either 3/8" or John Guest connections). This guarantees you an optimum water quality for every application (coffee and espresso machines, vending machines, combi ovens, conventional ovens and coolers).

## The benefits to you

- Various head designs for targeted adaptation to individual requirements
- Simple to handle with rapid-change system
- Innovative locking handle for reliable adjustment
- Water inlet and outlet on one filter head side for space-saving installation
- Integrated flush and bleed valve
- Simple pre-rinsing and bleeding
- Fast and convenient filter exchange without the need for tools
- Water short-cut if cartridge is not inserted



## BRITA Professional Filter Service App

The Filter Service App is your ideal assistant. This unique, comprehensive tool helps determine the right type and size of filter for your precise needs. It provides detailed installation guidance for service engineers, calculates when cartridges will need replacing - and has a wealth of other, innovative capabilities.

Download for free on



Or visit <https://professional.brita.net/app>



# Three simple steps for optimised water



Flush valve with convenient slider mechanism for all 0 - 70% filter heads

Available with two connections G3/8" and JG 8 mm

## Two minutes for your new water filter



To exchange the filter cartridge, rotate the locking handle to divert the water and release the cartridge. Press the flush valve and depressurise the filter. Remove the filter cartridge from the filter head.

The filter cartridge can be pivoted by 90° in the wall mounting bracket for removal. Remove the protective cap from the new filter cartridge. Note the next exchange date in the date field on the filter cartridge.

Insert the filter cartridge vertically into the filter head and turn the locking handle until you hear it click. Operate the flush valve and rinse the filter system until the filtered water runs clear without bubbles - done!

The food safety of BRITA Professional water filter products is tested and monitored by independent institutes.



\*applies to all materials in contact with water

PURITY C Filter Head system		Order number			
Filter head 0 % <sup>1</sup> (G 3/8"   JG 8)		1002949 (Pack 1)/297177 (Pack 20)*   1002942 (Pack 1)*/297176 (Pack 20)*			
Filter head 30 % <sup>2</sup> (G 3/8"   JG 8)		1002952 (Pack 1)/297175 (Pack 20)*   1002945 (Pack 1)*/297174 (Pack 20)*			
Filter head 0 - 70 % <sup>3</sup> (G 3/8"   JG 8)		1013637 (Pack 1)/1013634 (Pack 20)*   1013636 (Pack 1)* / 1013633 (Pack 20)*			
Filter head 0 - 3 C Steam <sup>4</sup> (G3/8")		1023325 (Pack 1)			
PURITY C Filter head set III 0 - 70 % (Filter head G 3/8", backflow preventer, CH test kit, wall mounting bracket)		1002937			
Accessories		Order number			
BRITA FlowMeter 10 - 100		1033041			
Backflow preventer G 3/8"		1000639 (Pack 3)			
Backflow preventer JG 8		292069 (Pack 1)*			
Products	Diameter	Connection	Length	Order number	
Hoses/Connection modules without arc	DN 13	3/4" - 3/4"	2.0 m	1007721	
	DN 8	3/4" - 3/8"	2.0 m	1007720	
	DN 8	3/4" - 3/4"	2.0 m	1007719	
	DN 8	3/4" - 3/4"	1.5 m	1007716	
	DN 8	3/8" - 3/8"	1.5 m	1007714	
	DN 8	3/4" - 3/8"	1.5 m	1007706	
Hoses/Connection modules with arc	DN 13	3/4" - 3/4" arc	2.0 m	1007725	
	DN 8	3/8" - 3/4" arc	1.5 m	1007724	
	DN 8	3/8" - 3/8" arc	1.5 m	1007722	
Arcs	-	3/4" arc	-	315648	
	-	3/8" arc	-	1007740	
Shut-off valves	-	1"	-	1007741	
	-	3/4"	-	1007743	
	-	3/8" with integrated backflow preventer	-	1007745	
Reducer Kits	-	3/8" female thread - 3/4" male thread	-	1000898	
	-	3/4" female thread - 3/8" male thread	-	364600	
Inlet hose DN 8 3/8" - 3/8" Shut-off valve	DN 8	3/8" - 3/8" Shut-off valve incl. backflow preventer	1.5 m	1007730	
Inlet hose DN 13 3/4" - 1" Shut-off valve	DN 13	3/4" - 1"	2.0 m	1007739	
Hose set I Shut-off valve, 3/4" - 1"	DN 8	3/4" - 3/8" (2x)	2.0 m	1007732	
Hose set II Shut-off valve, 3/4" - 1"	DN 8	3/4" - 3/4" (2x)	2.0 m	1007734	
Hose set III Shut-off valve, 3/4" - 1"	DN 13	3/4" - 3/4" (1x w. arc)	2.0 m	1007735	
Explanatory notes	<sup>1</sup> For coolers		<sup>3</sup> Can be used flexibly for all applications		
	<sup>2</sup> For coffee machines and vending machines		<sup>4</sup> To be used exclusively for the PURITY C Steam filter cartridges		
* Not available in Switzerland					

Only drinking water quality may be used as the water supply for BRITA water filters.

For more information please contact:

### BRITA Water Filter Systems Ltd.

BRITA House | 9 Granville Way | Bicester | OX26 4JT | United Kingdom  
Tel.: +44 844 742-4990 | Fax: +44 186 936-5962  
clientservices@brita.co.uk | www.brita.co.uk

### BRITA Water Filter Systems Distributors Pty Ltd

Suite 2, Level 9, 123 Epping Road | Macquarie Park, NSW, 2113 | Australia  
Tel.: +61 1300 955-021 | NZ: 0800 482-008  
professional@brita.com.au | www.brita.com.au

### Headquarters: BRITA SE

Heinz-Hankammer-Straße 1 | 65232 Taunusstein | Germany  
Tel.: +49 6128 746-0 | Fax: +49 6128 746-5033  
info@brita.net | www.brita.net

## BRITA Recycling Program

Environmental protection and recycling are part of the BRITA corporate philosophy. As early as 1992, we established a recycling programme for our filter cartridges - the first in our industry. Our plant in Taunusstein, Germany, processes cartridges from both the hospitality industry and private households.



Learn more about the BRITA Recycling program:  
[brita.co.uk/recycling-professional](http://brita.co.uk/recycling-professional)